

## **PLAYER SERIES – JRII/PB**

Recommended for filling SCUBA tanks and tanks of similar size for taking extra air into the field.

### **General Specifications and Standard Features**

- 4500 PSIG Maximum Operating Pressure
- 3-Stage Intermittent-Duty Rated Compressor
- Air-Cooled
- Splash Lubricated
- Air Processing System with Replaceable Cartridge
- Attended Manual Operation
  
- Inlet Filter
- Interstage Coolers
- Aftercooler
- Interstage Separator with Manual Drain
- Final Separator with Manual Drain
- Interstage Safety Valves
- Final Safety Valve
- Pressure Maintaining Valve
- Check Valve
- V-Belt Drive with Guard
- Cooling Fan with Guard
- Vibration Isolators
- Durable Painted Steel Frame with Carry Handle for Portability
- 5-Ft Fill Hose with Pressure Gauge, Venting Valve and SCUBA Connector

#### Disclaimers:

Capacity is referenced to standard inlet conditions and 80% of the compressor's maximum operating pressure.

Tolerance on capacity is +/- 5%.

1 Year Warranty.

Ambient Temperature Range: +40 to +113 °F

Dimensions and weight are approximate.

Use only with a suitable protected electric outlet installed by a licensed electrician.

Use gasoline engine only in a well ventilated area.

JRII/PB is recommended for filling SCUBA and similar size tanks.

JRII/PB is not recommended for filling paintball marker tanks directly.

JRII/PB is not recommended for tournament air supply or for most stores and fields.

Consult BAUER for sizing.

All information is subject to change without notice or obligation.