

CLASSIC II *Horizontal Design*

5-10 HP – ELECTRIC MOTOR DRIVE



CLASSIC II 5-10 HP Series combines compressor and air purification in a horizontal design which accommodates a 5000 or 6000 PSIG three or four stage compressor. Discharge capacities range from 5.0 SCFM Charge Rate up to 13.0 SCFM Charge Rate.



CLASSIC II - ES Series
Open Version



CLASSIC II - LS Series
Enclosed Version

MODEL	NUMBER OF STAGES	CHARGING RATE SCFM*	FAD **	HP	RPM	PURIFICATION SYSTEM	DIMENSIONS L - W - H INCHES	WEIGHT LBS.
-------	------------------	---------------------	--------	----	-----	---------------------	-----------------------------	-------------

5000 PSI SERVICE

CII-E1	3	6.0	5.0	5	1250	P0	53 - 35 - 33	690
CII-E3	3	6.0	5.0	5	1250	P0	53 - 35 - 33	690
MII-E1	3	8.4	7.0	7.5	1250	P31	53 - 35 - 33	705
MII-E3	3	8.4	7.0	7.5	1250	P31	53 - 35 - 33	705

6000 PSI SERVICE

H5-E1	3	5.0	4.0	5	1050	P41	53 - 35 - 33	710
H5-E3	3	5.0	4.0	5	1050	P41	53 - 35 - 33	710
H10-E1	4	9.7	8.1	7.5	1180	P41	53 - 35 - 33	745
H10-E3	4	9.7	8.1	7.5	1180	P41	53 - 35 - 33	745
H13-E1	4	13.0	10.8	10	1420	P41	53 - 35 - 33	750
H13-E3	4	13.0	10.8	10	1420	P41	53 - 35 - 33	750

*Based on recharging an 80 cubic foot tank from 500 to 3000 PSIG.

**Compressor capacity referenced to standard inlet conditions.

E3 = Three Phase Electric, 230/460 VAC/60 Hz.

Other voltages available on request.

Dimensions and weights are approximate and are subject to change.

STANDARD FEATURES – ES-ECONOMY SERIES

- Open Frame Design
- UL® Listed Electrical Assembly
- PLC Based Controller
- NEMA 4 Electrical Enclosure
- Final Pressure Switch
- Final Stage Pressure Gauge
- Low Oil Pressure Switch
- Oil Pressure Gauge
- Purification System Pressure Gauge
- High Temperature Switch
- Hourmeter

ADD TO ABOVE STANDARD FEATURES – LS-LUXURY SERIES

- Automatic Condensate Drain System with Float Switch in Condensate Drain Reservoir
- Upgrades to P43 with SECURUS Purification System Monitor
- Aesthetically Pleasing Cabinet Enclosure with Complete Gauge Panel including Interstage Pressure Gauges

CLASSIC II *Horizontal Design*

15-20 HP – ELECTRIC MOTOR DRIVE



If your need is for greater air requirements, **CLASSIC II** 15-20 HP Series combines compressor and air purification in a horizontal design which accommodates a 5000 or 6000 PSIG four or five stage compressor. Discharge capacities range from 19.2 SCFM Charge Rate up to 26.4 SCFM Charge Rate.



CLASSIC II - ES Series
Open Version



CLASSIC II - LS Series
Enclosed Version

MODEL	NUMBER OF STAGES	CHARGING RATE SCFM*	FAD **	HP	RPM	PURIFICATION SYSTEM	DIMENSIONS L - W - H INCHES	WEIGHT LBS.
5000 PSI SERVICE								
K20-E3	4	21.0	17.5	15.0	1300	P42	58 - 35 - 38	975
K26-E3	4	26.4	22.0	20.0	1350	P42	58 - 35 - 38	1055
6000 PSI SERVICE								
H19-E3	5	19.2	16.0	15.0	1050	P42	58 - 35 - 38	1065
H25-E3	5	25.2	21.0	20.0	1300	P42	58 - 35 - 38	1075

*Based on recharging an 80 cubic foot tank from 500 to 3000 PSIG.

**Compressor capacity referenced to standard inlet conditions.

E3 = Three Phase Electric, 230/460 VAC/60 Hz.

Other voltages available on request.

Dimensions and weights are approximate and are subject to change.

STANDARD FEATURES – ES-ECONOMY SERIES

- Open Frame Design
- P42 Purification System
- Automatic Condensate Drain System with Float Switch in Condensate Drain Reservoir
- UL® Listed Electrical Assembly
- PLC Based Controller
- NEMA 4 Electrical Enclosure
- Final Pressure Switch
- Final Stage Pressure Gauge
- Low Oil Pressure Switch
- Oil Pressure Gauge
- Purification System Pressure Gauge
- High Temperature Switch
- Inlet Filter Maintenance Indicator
- Hourmeter

ADD TO ABOVE STANDARD FEATURES – LS-LUXURY SERIES

- SECURUS® Electronic Moisture Monitoring
- Aesthetically Pleasing Cabinet Enclosure with Complete Gauge Panel including Interstage Pressure Gauges