

MEDIUM PRESSURE**3-STAGE HIGH PRESSURE COMPRESSORS**

The medium pressure range of industrial air compressors from the technology leader in high pressure features continuous-duty rated, 3-stage, air cooled, pressure lubricated compressors for the most demanding requirements. The full-featured PLC control system with HMI allows for unattended, automatic operation. Heavy-duty frames and balanced compressor designs do not require a special foundation for installation.

› PRESSURE:


400 to 1000 PSIG
(28 to 69 BAR)

› CHARGING RATE:

7.5 to 240 SCFM
(212 to 6800 L/MIN)

› POWER:

5 to 150 HP
(3.7 to 110 kW)

**› B23.4**

STANDARD SCOPE OF SUPPLY

- › 3-stage, air cooled, pressure lubricated, continuous-duty rated reciprocating compressor
- › Electric motor with v-belt drive, belt guard and belt tensioning device
- › Automatic condensate drain with condensate collector (collector includes switch for high condensate level)
- › Automatic operation with PLC controller (includes operator keypad and text display for operation, maintenance and troubleshooting)
- › NEMA 4 rated electrical enclosure with UL listed control panel
- › Fused control voltage transformer
- › Hourmeter
- › Pressure sensors for oil pressure and final pressure
- › Temperature switch
- › Emergency stop push button
- › Audible alarm
- › Ambient temperature range 40° to 113° F
- › 24 month warranty

AVAILABLE ACCESSORIES

- › Enclosure

30 - 125 HP MODELS

- › Soft Starter
- › TEFC motor
- › Fused disconnect

TECHNICAL DATA

Model	Capacity FAD ¹		Number of Stages	Motor		Drive
	SCFM	L/MIN		HP ²	kW	
350 - 1000 PSIG (24 - 69 BAR)						
B12.4	7.5	212	3	5	3.7	E1/E3
B22.5	24 - 33	680 - 935	3	15 - 20	11 - 15	E3
B23.4	48 - 61	1360 - 1728	3	30 - 40	22 - 30	E3
B25.4	75	2125	3	50	37	E3
B28.2	100 - 113	2832 - 3200	3	60 - 75	45 - 55	E3
B28.3 ³	200 - 240	5665 - 6800	3	125 - 150	93 - 110	E3

1) Compressor capacity (FAD) is referenced to standard inlet conditions and 80% of the compressor's maximum working pressure. Tolerance +/- 5%.

2) 3-phase motors only, 60 Hz standard. 50 Hz available on request.

3) Maximum discharge pressure of 900 PSIG.

E1 = 230/1/60 E3 = 230 - 460/3/60 Other voltages and frequencies available upon request. Engine drives available.

BAUER COMPRESSORS, INC.

1328 Azalea Garden Road
Norfolk, VA 23502
Tel. +1 (757) 855-6006
Fax +1 (757) 857-1041

www.BauerComp.com



1098.06.19.150AP

Subject to technical changes