

## DDTR26-WRAF

Effective: 01/01/10

- › **Pressure**  
5000 psig (345 bar)
- › **Charging Rate**  
26.4 scfm (748 l/min)
- › **Power**  
27 hp (20 kW)
- › **Contract Period**  
08/27/97 - 08/26/12
- › **Modification PO18**  
Effective 30 December 2009



**GSA**

**Contract Holder**  
Contract #GS-07F-9711G



**SCHEDULE 084:** Total solutions for law enforcement, security, facilities management, fire, rescue, clothing, marine craft and emergency / disaster response.

**NAICS Code # 333912**

Our aesthetically pleasing enclosure encompasses the compressor system from inclement weather and road debris and the heavy-duty frame provides a firm foundation for up to four air storage cylinders. The single axle design enhances mobility with most smaller vehicles.

## DDTR26-WRAF

### STANDARD SCOPE OF SUPPLY

- › Manufactured in compliance with the National Trailer Manufacturers Association (NATM) guidelines
- › NFPA 1901 Compliant two position Containment Fill Station accommodates SCBA or SCUBA cylinders up to 31" overall length
- › Unique diesel drive system incorporating our exclusive automatic belt tensioning system
- › High gloss powder coat paint for a hard durable finish
- › Hydraulic surge brakes with breakaway actuator
- › Four (4) bank dual function cascade controls with air direction valve
- › Formed structural steel frame designed and built by BAUER
- › Hypalon® type cover protection for the operations panel and fill station
- › Refill port
- › Telescoping light mast with four (4) 500 watt fixtures, snorkel tube for compressor air inlet integrated with light mast and 7500 watt auxillary generator
- › 7.5 kW belt driven generator

### DIMENSIONS L x W x H inches (mm)

- › 176 x 94.25 x 81.25 (4470 x 2393.95 x 2063.75)

### WEIGHT pounds (kg)

- › 5500 (2495)

## Technical Data

Item	Model	Charging rate*		Number of stages	Motor		FAD**	RPM	Purification system
		scfm	l/min		hp	kW			
<b>5000 psig (345 bar) NSN 4310-01-515-9940</b>									
0001	DDTR26-WRAF	26.4	748	4	27	20	22	1300	P5 SECURUS

## Optional Accessories

Item	Description	Part number
0002	Spare tire and wheel chocks with fender well storage	OPTION PACKAGE A
0003	75 foot hose reel and interior lights	OPTION PACKAGE B
0004	2 5/16" ball hitch	OPTION PACKAGE C

\*Based on recharging an 80 cubic foot tank from 500 to 3000 psig. \*\*Compressor capacity referenced to standard inlet conditions. Dimensions and weight are approximate and are subject to change.

A. BAUER COMPRESSOR warranty includes parts and labor 12 Months from date of compressor start-up or 18 Months from date of shipment.

B. Spare parts consisting of normal wear and tear items; e.g., replacement cartridges, valve overhaul kits, gasket kits, belt, oil, inlet filter element, etc. are normal stock items at BAUER NORFOLK, BAUER SAN FRANCISCO and BAUER MIAMI.

### BAUER COMPRESSORS INC.

1328 Azalea Garden Rd. | Norfolk, VA 23502  
 TEL. +1 (757) 855-6006  
 FAX +1 (757) 857-1041  
[sls@bauercomp.com](mailto:sls@bauercomp.com)  
[www.bauercomp.com](http://www.bauercomp.com)

### CONTRACTOR ADMINISTRATOR

Brenda Allen  
 TEL. +1 (757) 857-8743  
 FAX +1 (757) 857-1041  
[brenda.allen@bauercomp.com](mailto:brenda.allen@bauercomp.com)

### DDTR26-WRAF

341.10.04.1SP

subject to alteration without notice or obligation