

JRII-E1/WT

Effective: 01/01/10

- > Pressure 3700 psig (255 bar)
- > Charging Rate 1.2 scfm (34 l/min)
- **Power** 1.5 hp (1.1 kW)
- >Contract Period 08/27/97 - 08/26/12
- Modification PO18
 Effective 30 December 2009







SCHEDULE 084: Total solutions for law enforcement, security, facilities management, fire, rescue, clothing, marine craft and emergency / disaster response.

NAICS Code # 333912

Provided with a 115 volt motor and 15 AMP plug, the JRII/WT is the ideal compressor for filling small high pressure cylinders used on less lethal launchers, weapons simulators, paintball markers, air rifles and pesticide injectors.

BAUER COMPRESSORS INC. JRII-E1/WT

JRII-E1/WT

STANDARD SCOPE OF SUPPLY

- Air-cooled high pressure JUNIOR compressor
- Electric motor 1.5 hp, 115 v
- ▶ BAUER PO air purification system to process 3,200 cf of air per cartridge at standard inlet conditions
- Pressure maintaining valve
- > Final pressure setting 3700 psig
- Check valve
- > Filter bleed valve
- > Air outlet, 1/4"
- Lightweight, fixed base
- **Hourmeter**
- Visual CO/Moisture monitor indicator

- > Inlet filter
- One 5 foot fill hose complete with shut-off valve, pressure gauge, vent valve and ADP-0097 adapter
- One 5 foot fill hose complete with shut-off valve, pressure gauge, vent valve and CGA 347 fill connector
- 10 foot electric cable with plug for 115 v 15 AMP circuit
- Base mounted on / off switch

DIMENSIONS L x W x H inches (mm) 29.375 x 14 x 16.25 (746.125 x 356 x 412.75)

WEIGHT pounds (kg)

) 100 (45)

Technical Data

Item	Model	Charging rate*		Number of stages	Motor		FAD**	RPM	Purification system	
		scfm	l/min		hp	kW				
3700 psig (255 bar)										
0001	JRII-E1/WT	1.2	34	3	1.5	1.1	1	2100	PO	

Optional Accessories

Item	Description	National stock number	Part number
0002	Replacement purification cartridge	NSN 4330-01-350-9101	059183A
0003	Gasket kit		N06406
0004	Valve overhaul kit	NSN 4820-01-448-1600	N05457
0005	Inlet filter element	NSN 4310-01-447-5922	N04823
0006	Fill gauge		GAG-0010W
0007	Fill hose 5 foot		HOS-0123

^{*}Based on recharging an 80 cubic foot tank from 500 to 3000 psig. **Compressor capacity referenced to standard inlet conditions. Dimensions and weight are approximate and are subject to change.

BAUER COMPRESSORS INC.

1328 Azalea Garden Rd. | Norfolk, VA 23502 Brenda Allen

TEL. +1 (757) 855-6006

FAX +1 (757) 857-1041

sls@bauercomp.com www.bauercomp.com

CONTRACTOR ADMINISTRATOR

TEL. +1 (757) 857-8743 FAX +1 (757) 857-1041

brenda.allen@bauercomp.com

JRII-E1/WT 353.10.04.1SP

subject to alteration without notice or obligation

A. BAUER COMPRESSOR warranty includes parts and labor 12 Months from date of compressor start-up or 18 Months from date of shipment.

B. Spare parts consisting of normal wear and tear Items; e.g., replacement cartridges, valve overhaul kits, gasket kits, belt,

oil, inlet filter element, etc. are normal stock items at BAUER NORFOLK, BAUER SAN FRANCISCO and BAUER MIAMI.